

PRODUCT DATA SHEET

| | |
|---------------------------|--|
| Product | Quick Drying Radiator Enamel |
| Type | Formulated with a special non-yellowing, acrylic emulsion and high quality white pigment (titanium dioxide) to produce a brilliant white finish that will not yellow on hot radiators. |
| Intended Use | For domestic hot water radiators. Not suitable for electric oil-filled radiators (max temp 90°C). |
| Special Features | Non-yellowing. Quick drying. Low odour. Clean brushes in water. May also be used on wood as a topcoat and as a touch-up on white equipment such as refrigerators but not for use on stoves. |
| Preparation | The surface must be clean, smooth, sound, dry, free from wax, dust and contaminants. If the radiator is new and factory primed, apply 1 coat of Rustins White Oil-based Undercoat before applying the radiator paint. Radiators stripped to bare metal should be given one coat of Rustin's Red Oxide Metal Primer and one coat of oil based white undercoat or Rustin's Quick Dry White Primer/Undercoat . If oil based undercoat is used leave for 24 hours |
| Application | Stir well before use. Allow radiators to cool before painting. Apply liberally and evenly with a synthetic fibre brush. Radiators can be used between coats if necessary. Leave to dry for 2 hours before turning on radiator. |
| Coats | 1 or 2 coats as required. |
| Drying Time | Touch dry within 30 minutes, depending on temperature and humidity. |
| Re-coating Time | Allow 4 hours between coats, depending on temperature and humidity. |
| Application Temp. | Ideally 15-25°C. Do not use below 10°C or in conditions of high humidity. |
| Coverage | Approximately 14 sq. metres/litre per coat. |
| Maintenance | Clean painted surfaces with a mild detergent solution. |
| Compatibility | Can be applied over Rustin's Quick Drying Primer & Undercoat and Rustin's White Undercoat . |
| Settlement | STIR WELL BEFORE USE. Satin finishes may dry glossy if not stirred thoroughly. |
| Shelf-life/Storage | Many years if stored in original tightly closed container in normal conditions. Do not store below 5°C. Protect from frost. |
| Hazards | Non-flammable. Flash point Nil. Avoid contact with eyes and skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical attention. After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleanser. Keep out of reach of children. A full Safety Data Sheet is available upon request or on www.rustins.co.uk |
| Clean-Up | Clean brushes and hands immediately after use with water. If dried on, clean equipment and brushes with Rustin's Brush Restorer . |
| Sizes | 250ml 500ml 1 L |