

BRIWAX SPRAYWAX

Page: 1

Compilation date: 10/03/2015 Revision date: 08/01/2020

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: BRIWAX SPRAYWAX

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Rustins Ltd

Waterloo Road Cricklewood London NW2 7TX United Kingdom Tel: +44 (0)208 450 4666 Fax: +44 (0)208 452 2008 Email: rustins@rustins.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0)208 450 4666 OFFICE HOURS ONLY

Section 2: Hazards identification

2.1. Classification of the sub-	stance or mixture
Classification under CLP:	Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Flam.
	Aerosol 1: H222; STOT SE 3: H336; -: EUH066; -: H229
Most important adverse effects:	Repeated exposure may cause skin dryness or cracking. Extremely flammable aerosol.
	Pressurised container: May burst if heated. Causes skin irritation. May cause an allergic
	skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness.
	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements:	EUH066: Repeated exposure may cause skin dryness or cracking.	
	H222: Extremely flammable aerosol.	
	H229: Pressurised container: May burst if heated.	
	H315: Causes skin irritation.	
	H317: May cause an allergic skin reaction.	
	H319: Causes serious eye irritation.	
	H336: May cause drowsiness or dizziness.	
	H412: Harmful to aquatic life with long lasting effects.	[coi

BRIWAX SPRAYWAX

Page: 2

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark



Signal words: Danger

Precautionary statements:	P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition
	sources. No smoking.
	P211: Do not spray on an open flame or other ignition source.
	P251: Do not pierce or burn, even after use.
	P280: Wear protective gloves and eye protection.
	P302+P352: IF ON SKIN: Wash with plenty of water.
	P362+P364: Take off contaminated clothing and wash it before reuse.
2.3. Other hazards	

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

BUTANE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
203-448-7	106-97-8	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	35.000%

BAS30

Flam. Liq. 3: H226; STOT SE 3: H336; 30.000% Asp. Tox. 1: H304; -: EUH066
--

PROPANE

200-827-9	74-98-6	Substance with a Community	Flam. Gas 1: H220; Press. Gas: H280	28.800%
		workplace exposure limit.		

LEMON SODA FRAGRANCE

-	-	-	Eye Irrit. 2: H319; Skin Sens. 1: H317;	1.000%
			Aquatic Chronic 1: H410; Asp. Tox. 1:	
			H304; Skin Corr. 1A: H314; Skin Irrit. 2:	
			H315	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water. Consult a doctor.

BRIWAX SPRAYWAX

Page: 3

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: Exposure may cause coughing or wheezing.

Delayed / immediate effects: Delayed effects can be expected after long-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Do not attempt to take action without suitable protective clothing - see section 8 of SDS.

Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

BRIWAX SPRAYWAX

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

BUTANE

Workplace e	xposure limits:		Respirable dust	
State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1450 mg/m3	1810 mg/m3	-	-

PROPANE

UK 1800 mg/m3 7200 mg/m3	UK	1800 mg/m3	7200 mg/m3	-	-
--------------------------	----	------------	------------	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures:Ensure there is sufficient ventilation of the area.Respiratory protection:Self-contained breathing apparatus must be available in case of emergency.Hand protection:Impermeable gloves.Eye protection:Safety glasses. Ensure eye bath is to hand.Skin protection:Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Aerosol
Colour:	Colourless
Odour:	Aromatic
Evaporation rate:	No data available.
Oxidising:	No data available.
Solubility in water:	Slightly soluble
Also soluble in:	Most organic solvents.
Viscosity:	Viscous

Page: 5

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Boiling point/range°C:	No data available.	Melting point/range°C:	No data available.
Flammability limits %: lower:	No data available.	upper:	No data available.
Flash point°C:	<23	Part.coeff. n-octanol/water:	No data available.
Autoflammability°C:	No data available.	Vapour pressure:	No data available.
Relative density:	1.0	pH:	Approx. 7
VOC g/l:	No data available.		

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Relevant hazards for product:

Symptoms / routes of exposure

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

[cont...]

BRIWAX SPRAYWAX

Page: 6

Inhalation: Exposure may cause coughing or wheezing.

Delayed / immediate effects: Delayed effects can be expected after long-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

asphyxiant

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

Packing group: |||

BRIWAX SPRAYWAX

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information	
Other information:	according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation
	(EU) 2015/830
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	EUH066: Repeated exposure may cause skin dryness or cracking.
	H220: Extremely flammable gas.
	H222: Extremely flammable aerosol.
	H226: Flammable liquid and vapour.
	H229: Pressurised container: May burst if heated.
	H304: May be fatal if swallowed and enters airways.
	H315: Causes skin irritation.
	H317: May cause an allergic skin reaction.
	H319: Causes serious eye irritation.
	H336: May cause drowsiness or dizziness.
	H410: Very toxic to aquatic life with long lasting effects.
	H412: Harmful to aquatic life with long lasting effects.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.