



# Technical Data Sheet

## Blackfriar Multi-Surface Primer

**Blackfriar Multi-Surface Primer** has been specially formulated to prime multiple surfaces prior to further painting. It's ideal for hard and soft woods, chipboard, plywood, GRP, MDF, exterior UPVC, ceramic tiles, iron, steel, galvanised and non-ferrous metals (aluminium, brass, chrome, copper) and old plaster. It contains an anti-corrosive pigment to protect iron and steel.

### Performance characteristics –

- Interior and exterior use.
- For multiple surfaces prior to painting.
- Anti-corrosive protection.

**Preparation** - Ensure the surface to be primed is clean, dry, sound and free from wax, grease and oil. If you are preparing wood or plaster, remove loose/ flaking paint, clean to a bare surface and sand smooth. Remove any fungal growth or mould with Blackfriar Concentrated Fungicidal Wash prior to application. Treat any knots or resinous wood with Blackfriar Patent Knotting and allow to dry before applying Blackfriar Multi-Surface Primer. If preparing iron and steel, remove any rust and mill scale with a wire brush, clean back to a bright surface, and prime immediately.

**Application** - Stir thoroughly before use. Apply one coat of product by brush or roller except on ferrous metals and porous surfaces where two coats are required. For porous surfaces, dilute the first coat with 10% water. If applying two coats lightly sand the first coat prior to applying the second to remove any imperfections. Please note when applying to copper, the primer coat may turn blue - this colour will not be visible once a top coat is applied.

**Coverage** - Up to 12m<sup>2</sup> per litre per coat. Coverage may vary depending on method, rate of application and roughness of surface.

**Drying Time** - Touch dry in 1 hour. Apply a second coat after 4 hours if required. Drying times will be extended in

low temperatures. Not recommended for use in damp conditions or if the temperature is below 10°C.

**Clean Up** - Remove as much paint as possible from equipment before cleaning. Clean with warm water, rinse and dry thoroughly.

**Storage** - Store in a dry, safe place. Do not store in environments where extreme temperatures may occur. Keep within 5-30°C. Do not store in direct sunlight.

Keep out of reach of children.

Read label before use.

If medical advice is needed: Have product container or label at hand.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Contains Reaction mass of:

5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

Safety data sheet available on request.

EU limit values for this product: (Cat IIA/g): 50g/l (2007) 30g/l (2010.) This product contains a max. of 30g/l VOC.

Whilst every effort is made to ensure the accuracy of colour, due to limitations of the print process, colour / finish shown is for guidance only.