

**DESCRIPTION**

Johnstone's Aqua Water Based Gloss is an innovative water based gloss with a high sheen finish, ideal for interior and exterior wood and metal. Specially formulated to give all the application and appearance characteristics of traditional gloss with the added advantage of being quick drying and low odour during application. Johnstone's Aqua Water Based Gloss should be used in conjunction with Johnstone's Aqua Water Based Undercoat to give the best possible finish.

**RECOMMENDED USES**

Suitable for interior and exterior use.

**TYPE OF SUBSTRATE**

Ideal for interior and exterior wood and metal.

**COLOUR RANGE**

Over 16,000 colours are available via the Johnstone's Tinting System.

**FINISH**

Gloss.

**VOLUME SOLID**

41.9%

**COVERAGE**

Approximately 10–12 square metres per litre depending on the nature and porosity of the surface being painted.

**DRYING TIME\***

Touch dry in 1–2 hours.  
Recoat after 4-6 hours.

**TRANSPORTATION & STORAGE**

Avoid the risk of spillage, always store and transport in a secure upright position. Protect from frost.

**CLEANER**

Clean water.

**VOC CONTENT**

Low VOC content 0.30-7.99%  
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 130g/l (2010).  
This product contains max 50g/l VOC.

**FILM THICKNESS**

Wet: 91µm, dry: 38µm.

**KEY PROPERTIES**

- Applies and finishes more like a solvent based gloss.
- Quick drying.
- Low odour.
- Lesser yellowing than a solvent based gloss.

**PREPARATION**

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare wood surfaces with Johnstone's Aqua Water Based Undercoat. Prime all other bare surfaces with the appropriate Johnstone's primer. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory, on 01924 354354.

**APPLICATION**

Stir well before use. Easy to apply by brush.  
Avoid overspreading. Do not apply in temperatures below 10°C or externally when rain is imminent.  
For best results use a good quality synthetic brush.

**CLEANING**

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

**PRECAUTIONS**

- Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Safety data sheet available on request.

**SIZES**

1 Litre, 2.5 Litre, 5 Litre.