

Printing date 22.01.2020 Version number 15.2 Revision: 22.01.2020

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Osmo TopOil

Article number: 3028 Clear Satin, 3037 White, 3038 Terra, 3039 Graphite, 3058 Clear Matt,

3061 Acacia, 3068 Natural

1.2 Relevant identified uses of the substance or mixture

and uses advised against No further relevant information available.

Application of the substance

/ the mixture Paint

Coating compound/ Surface coating/ paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG

Affhüppen Esch 12 D-48231 Warendorf

Further information

obtainable from: Product safety department

Tel.: +49 (0) 251 / 692 - 188 Fax: +49 (0) 251 / 692 - 462 e-mail: helmut.starp@osmo.de

1.4 Emergency telephone

number: emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in

German and English

#### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to

Regulation (EC) No 1272/2008 The product is not classified, according to the CLP regulation.

2.2 Label elements

Hazard pictogramsVoidSignal wordVoidHazard statementsVoid

**Precautionary statements** P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P262 Do not get in eyes, on skin, or on clothing.
P271 Use only outdoors or in a well-ventilated area.

**Additional information:** EUH210 Safety data sheet available on request.

**2.3 Other hazards** Observe the general safety regulations when handling chemicals.

Always wear a dust mask when sanding.

Warning:

Wash out any used cloth impregnated with this product immediately after use

or store in an airtight container (danger of self-ignition)

Results of PBT and vPvB assessment

**PBT:** Not applicable.

(Contd. on page 2)



Printing date 22.01.2020 Version number 15.2 Revision: 22.01.2020

Trade name: Osmo TopOil

(Contd. of page 1)

*vPvB:* Not applicable.

#### SECTION 3: Composition/information on ingredients

3.2 Mixtures

**Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

EC number: 918-481-9 aliphatic hyd

aliphatic hydrocarbons, C10-C13

Asp. Tox. 1, H304

25-50%

Reg.nr.: 01-2119457273-39

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

4.1 Description of first aid measures

**General information:** Take affected persons out into the fresh air.

Immediately remove any clothing soiled by the product.

**After inhalation:** Supply fresh air. If required, provide artificial respiration. Keep patient warm.

Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for

transportation.

**After skin contact:** Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a

doctor.

After swallowing: If symptoms persist consult doctor.

Do NOT induce vomiting.

4.2 Most important symptoms

and effects, both acute and

delayed No further relevant information available.

4.3 Indication of any

immediate medical attention

and special treatment needed No further relevant information available.

### SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing

agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol

resistant foam.

For safety reasons unsuitable

extinguishing agents: Water with full jet

(Contd. on page 3)



Printing date 22.01.2020 Version number 15.2 Revision: 22.01.2020

Trade name: Osmo TopOil

(Contd. of page 2)

5.2 Special hazards arising

from the substance or

mixture

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

Protective equipment:

Mouth respiratory protective device.

Additional information Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with

official regulations.

#### SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and

emergency procedures

Ensure adequate ventilation

Keep away from ignition sources.

6.2 Environmental

precautions:

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for

containment and cleaning up: Warm water and cleansing agent

Absorb with liquid-binding material (sand, diatomite, acid binders, universal

binders).

6.4 Reference to other

sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### SECTION 7: Handling and storage

7.1 Precautions for safe

**handling** Use only in well ventilated areas.

Keep receptacles tightly sealed. No special measures required.

Information about fire - and

explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by

storerooms and receptacles: Store only in the original receptacle.

Information about storage in

one common storage facility: Not required.

Further information about

storage conditions: None.

Storage class: VCI storage class (VCI = German Association of the Chemical Industry): 10

(Contd. on page 4)



Printing date 22.01.2020 Version number 15.2 Revision: 22.01.2020

Trade name: Osmo TopOil

(Contd. of page 3)

7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

Additional information about

design of technical facilities: No further data; see item 7.

8.1 Control parameters Ingredients with limit values that require monitoring at the

workplace: The product does not contain any relevant quantities of materials with critical

values that have to be monitored at the workplace.

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

General protective and

hygienic measures: Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

Respiratory protection: Not necessary if room is well-ventilated.

> Use suitable respiratory protective device only when aerosol or mist is formed. Use a properly fitted, air-purifying or air-fed repirator complying with an approved standard if a risk assessment indicates this is necessary. Half mask with round thread connection EN 148-1 (screw-on filter) and

combination filter A1 - P2 according to German DIN EN 14387.

Protection of hands: To avoid skin problems reduce the wearing of gloves to the required minimum.

The glove material has to be impermeable and resistant to the product/ the

substance/ the preparation.

Material of gloves The selection of the suitable gloves does not only depend on the material, but

> also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be

checked prior to the application.

Penetration time of glove

material

The exact break trough time has to be found out by the manufacturer of the

protective gloves and has to be observed.

For the permanent contact gloves made of the following

materials are suitable: Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6). (Contd. on page 5)



Printing date 22.01.2020 Version number 15.2 Revision: 22.01.2020

Trade name: Osmo TopOil

(Contd. of page 4)

For the permanent contact of a maximum of 15 minutes gloves made of the following

materials are suitable: Nitrile rubber, NBR

As protection from splashes gloves made of the following

materials are suitable: Nitrile rubber, NBR

**Eye protection:** Goggles recommended during refilling

**Body protection:** Not required.

Protective work clothing

#### SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

**General Information** 

Appearance:

Form: Viscous

**Colour:** According to product specification

Odour: Mild

Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: > 180 °C (DIN 51751)

Flash point: > 60 °C (DIN EN ISO 2719)

*Ignition temperature:* 240 °C

**Auto-ignition temperature:** Product is not selfigniting.

**Explosive properties:** Product does not present an explosion hazard.

**Explosion limits:** 

 Lower:
 0.6 Vol %

 Upper:
 7.0 Vol %

Vapour pressure: Not determined.

**Density at 20 °C:** 0.92-0.97 g/cm³ (DIN 51757)

Solubility in / Miscibility with

water: Not miscible or difficult to mix.

Viscosity:

Dynamic at 20 °C: 140 mPas

Kinematic at 20 °C: 40-70 s (DIN EN ISO 2431/4mm)

>21 mm<sup>2</sup>/s (40°C)

(Contd. on page 6)



Printing date 22.01.2020 Version number 15.2 Revision: 22.01.2020

Trade name: Osmo TopOil

(Contd. of page 5)

Solvent content:

VOC (EC) Not applicable.

**9.2 Other information**No further relevant information available.

### SECTION 10: Stability and reactivity

**10.1 Reactivity** No further relevant information available.

10.2 Chemical stability Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous

**reactions** Reacts with fabric soaked in the product (e.g. cleaning wool).

10.4 Conditions to avoid No further relevant information available.10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous

decomposition products: Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Additional information:

Warning:

Wash out any used cloth impregnated with this product immediately after use

or store in an airtight container (danger of self-ignition)

#### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

#### LD/LC50 values relevant for classification:

#### aliphatic hydrocarbons, C10-C13

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rat)
Inhalative	LC50 / 4h	>5 mg/l (rat)

Primary irritant effect:

**Skin corrosion/irritation** At long or repeated contact with skin it may cause dermatitis due to the

degreasing effect of the solvent.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin

**sensitisation** Based on available data, the classification criteria are not met.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicityBased on available data, the classification criteria are not met.CarcinogenicityBased on available data, the classification criteria are not met.Reproductive toxicityBased on available data, the classification criteria are not met.STOT-single exposureBased on available data, the classification criteria are not met.

(Contd. on page 7)



Printing date 22.01.2020 Version number 15.2 Revision: 22.01.2020

Trade name: Osmo TopOil

(Contd. of page 6)

STOT-repeated exposure Aspiration hazard Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.

#### SECTION 12: Ecological information

#### 12.1 Toxicity

Aquatic toxicity:

aliphatic hydrocarbons, C10-C13

EC50 / 48h | >1,000 mg/l (daphnia) IC50 / 72h | >1,000 mg/l (algae) LC50 / 96h | >1,000 mg/l (fish)

12.2 Persistence and

**degradability** No further relevant information available.

12.3 Bioaccumulative

potential No further relevant information available.12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly

hazardous for water

12.5 Results of PBT and vPvB assessmentPBT: Not applicable.vPvB: Not applicable.

**12.6 Other adverse effects** No further relevant information available.

#### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

**Recommendation** Smaller quantities can be disposed of with household waste.

08 01 12 waste paint and varnish other than those mentioned in 08 01 11

15 01 04 metallic packaging

Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations.

#### **SECTION 14: Transport information**

14.1 UN-Number

ADR, ADN, IMDG, IATA Not applicable

(Contd. on page 8)



Printing date 22.01.2020 Version number 15.2 Revision: 22.01.2020

Trade name: Osmo TopOil

(Contd. of page 7)

14.2 UN proper shipping name

ADR, ADN, IMDG, IATA Not applicable

14.3 Transport hazard class(es)

ADR, ADN, IMDG, IATA

Class Not applicable

14.4 Packing group

ADR, IMDG, IATA Not applicable

14.5 Environmental hazards:

Marine pollutant: No

**14.6 Special precautions for user** Not applicable.

14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

UN "Model Regulation": Not applicable

#### SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations:

GISBAU-Code GISCODE: Ö60 VOC (EC) Not applicable.

15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Relevant phrases** H304 May be fatal if swallowed and enters airways.

**Department issuing SDS:** product safety department

Contact: Hr. Dr. Starp

Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European

Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

(Contd. on page 9)



Printing date 22.01.2020

Version number 15.2

Revision: 22.01.2020

Trade name: Osmo TopOil

(Contd. of page 8)

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Asp. Tox. 1: Aspiration hazard – Category 1

\* Data compared to the previous version altered.

- GE